

APPLICATION FOR  
UNITED STATES LETTERS PATENT  
SPECIFICATION

INVENTOR(s): Koujirou Ogura

Title of the Invention: SYSTEM AND METHOD FOR AUTOMATICALLY  
SETTING APPLETT LATEST VERSION

**SYSTEM AND METHOD FOR AUTOMATICALLY SETTING APPLET  
LATEST VERSION**

**Background of the Invention**

**5 Field of the Invention**

The present invention relates to an applet latest version automatically setting system and method for automatically setting the latest version of an applet such as a Java applet, etc. at a request of a client.

**Description of the Prior Art**

An applet program operated on different pieces of software is used in the current computer technology. Especially, a Java applet is expressed in a Java language, incorporated into an HTML file, and executed on a Web server.

Conventionally, the above mentioned Java applet is downloaded by a server when a client invokes a Web page, and is cached and used on the Java virtual machine of the Web browser. Normally, the Java applet is downloaded and used on the main memory of a client, but can be temporarily stored on a disk (hard disk, etc.) of a client, and then transmitted to the main memory for execution.

However, in the conventional system, after transmitting an applet to a client, the applet on the server side can be rewritten as the latest version. In this case, normally, the update of an  
5 applet is not notified to the client. Therefore, the client performs a process using an applet of an old version.

In such a case, the already cached and operated applet is updated by the browser using a  
10 button, and an applet can be read again. However, the server cannot predict when the version of an applet is updated, thereby performing an inefficient operation. In addition, depending on the setting of a browser, only an applet written to,  
15 for example, a disk can be read although a cached applet is re-read without updating the version of the applet.

### Summary of the Invention

20 The present invention has been developed to solve the above mentioned problems, and aims at providing a system and a method for automatically setting the latest version of an applet by storing a program for updating the version in the method  
25 for the applet, and realizing the update of the

version of the applet in the process of the applet itself.

That is, the above mentioned purpose can be attained by the present invention by providing an applet latest version automatically setting system including: a server having an applet storage unit for storing an applet of the latest version, and a version number storage unit for storing the version number of an applet stored in the applet storage unit; and a client having a version number information storage unit for performing a process based on the applet read from the server, and storing the version number information about the applet, a comparison unit for reading the version number information about the applet of the latest version from the version number storage unit when a predetermined event occurs, and comparing the read information with the version number information stored in the version number information storage unit, and an update unit for reading the applet of the latest version from the applet storage unit and updating the applet when the comparison process outputs a non-matching result.

The applet stored in the applet storage unit is, for example, a program written in the Java

language, and is sequentially updated, thereby storing the applet of the latest version. In addition, the version number information storage unit stores the version number information about  
5 the applet of the latest version.

For example, the server storing the above mentioned applet of the latest version can be a Web server, and communications are established between the server and the Web browser set for the client.

10

#### **Brief Description of the Drawings**

FIG. 1 shows the configuration of the system of the applet latest version automatically setting system according to an embodiment of the present  
15 invention;

FIG. 2A shows the configuration of the memory area in which the version number information about the latest version is entered;

FIG. 2B shows an example of actual data  
20 written to a memory area;

FIG. 3 shows the configuration of the system according to an embodiment of the present invention which is applied to a sales office server and a window terminal;

25 FIG. 4 is a flowchart of the processing

operations according to an embodiment of the present invention;

FIG. 5 is a flowchart of the processing operations in the initial method;

5        FIG. 6 is a flowchart of the processing operations in the starting method;

FIG. 7 is a flowchart of the version number checking process;

10       FIG. 8 is a flowchart of the version number inquiring method;

FIG. 9 shows the link mechanism on the right;

FIG. 10 is an oblique view of the link mechanism; and

15       FIG. 11 shows an example of a case in which a storage medium is used.

#### **Description of the Preferred Embodiment**

The embodiments of the present invention are described below by referring to the attached  
20 drawings.

FIG. 1 shows the configuration of the applet latest version automatically setting system according to the an embodiment of the present invention. In FIG. 1, the system includes a server  
25 1 and a client 2 connected to the server 1. A

plurality of clients 2 are practically connected to the server 1, but the connection to one client is shown in FIG. 1. A Web server 3 is set in the server 1. Memory 4 in which the applet program of the latest version is entered, and a version number file 5 in which the version number information about a corresponding latest applet is entered are set in the Web server 3. The applet entered in the memory 4 is a program for driving the Java, and the applet drives the Java virtual machine described later and performs a process.

The version number information about the latest version is stored in the version number file 5 in, for example, the format shown in FIG. 2. FIG. 2A shows the memory format of the version number file 5 configured by 4 bytes with the lower 2 bytes indicating version information and the higher 2 bytes indicating level information. For example, the version number 'V20L10' shown in FIG. 2B indicates the applet of the latest version having the version number is 20, and the level is 10. Therefore, in this case, as shown in FIG. 2B, the version area of the version number file 5 stores 14, and the level area stores 0A. The above mentioned level indicates, for example, a development number

in the same version. According to the present invention, it is not always necessary to include a level in the latest version.

On the client 2 side, the software of a Web browser 6, a Java virtual machine (VM) 7, and an applet 8 are set. The applet 8 is entered in a cache area 9. The version number information about the applet being operated is stored in a process unit 10. For example, the version number information storage area is set at a predetermined address.

The Web browser 6 displays the image of the data in the HTML (hyper text markup language) format provided from the Web server 3, and the applet (Java applet) 8 performs a process using the Java virtual machine 7. The above mentioned applet reads the applet of the latest version from the server 1 in the method described later, and updates the applet written in the cache area 9. A display (DSP) 2' displays according to the operation of the above mentioned applet.

FIG. 3 shows an example in which the relationship between the above mentioned server 1 and the client 2 is applied to the sales office server and the window terminal of a bank. A sales



office server 11 corresponds to the server 1, and a window terminal 12 corresponds to the client 2. The sales office server 11 has the Web server 3, the memory 4, and the version number file 5 as described above, and CORBR (common object request broker architecture) communications are established between the server and the window terminal 12. To attain this, a cooperative application 13 for establishing the CORBR communications is also installed.

In addition, the above mentioned Web browser 6 is mounted on the window terminal 12 so that the system can be activated by an operator 14. In addition, the applet used in this case relates to banking operations, and has the displays and functions required by the operator at the window of a bank.

In the applet latest version automatically setting system with the above mentioned configuration, the processing operations are performed as described below.

FIG. 4 is a flowchart of the processing operations according to the present invention, and shows the main process of an applet. In the following explanation, the Web server 3 of the

sales office server 11 which is the server 1, and the Web browser 6 of the window terminal 12 which is the client 2 have already been activated

First, an initializing process is performed  
5 (step (hereinafter expressed by S) 1). This initializing process (init) activates the Web browser 6, reads the applet from the server 1, and loads the applet of the latest version to the cache area 9 in the client 2 (window terminal 12). Then,  
10 practically, the initial method shown in FIG. 5 is performed. That is, the constant/variable initializing process is performed (S2), and the version number of the applet loaded on the cache area 9 is set. In this case, for example, when the  
15 current version of the applet is 'V20L10' as shown in FIG. 2, the data of '140A' is written. Then the applet initializing process is performed (S3). Next, the version number checking process is performed (S4). The version number checking process is  
20 performed when an applet is started, and is performed in the process of the applet starting method. FIG. 6 shows the process, and the version number checking process is performed in the starting method (S4'). Therefore, this process is  
25 described by referring to the version number

checking process (start).

FIG. 7 is a flowchart practically showing the version number checking process. First, the version number is inquired of the server 1 (sales office server 11) (S5). Then, it is compared with the version number information stored in the memory of the server 1 (S6). If the version number of the applet read to the client 2 is smaller than the version number of the server 1 (version number of client < version number of server), then the terminating process described later is performed (YES in S7).

FIG. 8 is a flowchart of the server version number inquiring process and the server version number reading process. This process is performed according to the server version number inquiring method. This process is performed by initializing the CORBA communications on the client 2 (window terminal 12) side (S5-1), and the client is connected to the server 1 (sales office server 11 (S5-2)). Then, the version number information about the applet is read from the version number file 5 in the sales office server 11 (S5-3).

In this case, the version number file 5 in the server 1 (sales office server 11) is opened (S5-4),

and the version number file is read (S5-5). Then, the read version number information is written (S5-6), and the version number file is closed (S5-7). Then, the version number of the server is set in  
5 the out-parameter (S5-8), the server 1 (sales office server 11) is disconnected (S5-9), and the post-CORBA communications process is performed (S5-10).

Thus, the version number inquiring process is  
10 performed as described above. However, the version number checking process (start) is performed when the starting method process is performed after the applet initialization, and the version number of the applet read by the Web server 3 matches the  
15 version number of the server 1 (version number of client = version number of server). Therefore, the determination (S7) is N (NO). As a result, in the version number checking process in the starting method, an event waiting state is entered (S8).

20 Then, a normal transaction is started. For example, the client 2 (window terminal 12) requests the server 1 (sales office server 11) to perform a process online. Depending on the contents of the operation, the process is performed offline, and  
25 can be performed only by the window terminal 12.

During the process, the occurrence of an event is awaited (N in S8 and S9). When an event occurs (Y (YES) in S9), it is determined whether or not it is a user event (S10). If it is a user event, it is  
5 furthermore determined whether or not an online process is required (S11). A user event refers to a process requiring the above mentioned online process, and the client is connected to the server 1 (sales office server 11) to use the application  
10 of the server 1.

In this case, the version number checking process (S12) is first performed. The version number checking process (S12) is performed according to the flowchart shown in FIG. 7. That is,  
15 the version number is inquired of the server 1 (S5), the version number data is compared (S6), and the version number about the applet is compared with the version number of the server 1 to know whether of not the version number of the client is smaller  
20 than the version number of the server 1 (version number of client < version number of server) (S7). The version number inquiring process is performed according to the above mentioned version number inquiring method (S5-1 through S5-10 shown in FIG.  
25 8).

As a result of the above mentioned process, the version number information read to the version number file is compared with the version number of the currently read applet. If the version numbers  
5 match each other, the user-specified event process is performed (S13), control is returned to the event wait state (S9). In this case, the version number of the applet entered in the server 1 (sales office server 11) is not updated, the version  
10 number of the server is equal to the version number of the applet of the client 2 (window terminal 12), the applet used in the current client 2 is the latest applet, the applet is not updated, and the current applet performs a terminal operations.

15 FIG. 9 shows a type of the above mentioned process. In this case, the version number memory of the server 1 (sales office server 11) stores the applet of the latest version, and the version number of the applet is not updated. Therefore, the  
20 version number information maintains as is. As a result, the above mentioned version number information inquiring process (1 shown in FIG. 9) is performed, it is determined whether or not the version numbers match each other, and the  
25 transaction starting process is performed (2 shown

in FIG. 9).

On the other hand, if the version number of the client is smaller than the version number of the server (Y (YES) in S7) in the above mentioned  
5 determining process (S7), then it is determined that the version number of the applet is updated, and the terminating process is performed (S14). This process is a destroying process (S14), the  
10 program of the applet stored in the cache area 9 is removed, and the applet of the latest version is read from the server 1 (S15).

The version number information about a corresponding version is read from the version number file 5, and written to the memory of the  
15 client 2. For example, updated data of '1500 or '140B' is written to the memory.

In the above mentioned process, when an event occurs, but not in an online process (N (NO) in S11), for example, when a process is performed with  
20 control passed to another Web page not using an applet, a corresponding user event process is performed (S16).

On the other hand, if the Web server 3 displays another Web page, or if the browser is  
25 displayed as an icon, an applet is in an inactive

state. If control is returned to the Web page or a browser displayed as an icon is restored, then a system event occurs (N (NO) in S10). In this case, it is determined whether or not the above mentioned starting event is being performed (S17).

If the starting method is activated (YES in S17), then the above mentioned version number checking process (start) is performed. This process is also performed according to the flowchart shown in FIG. 7, the version number inquiring process (S5, S5-1 through S5-10) and the comparing process are performed (S6 and S7). If the version number of the client is smaller than the version number of the server, then it is determined that the version number of the applet has been updated, and the terminating process is performed (Y (YES) in S7, S14). Therefore, in this case, the applet stored in the cache area 9 is deleted, the applet of the latest version is read from the server 1 and stored (S15). In addition, the version number information about the corresponding version is read from the version number file 5, and written to the memory of the client 2.

FIG. 10 shows a type of the above mentioned process. The applet of the server 1 (sales office



server 11) is updated, and the version number information is different. Therefore, the version number information inquiring process (1 shown in FIG. 10) is performed, and the version number  
5 information is rewritten (2 shown in FIG. 10).

By performing the above mentioned process, the memory of the client 2 (window terminal 12) stores an applet of the latest version, and based on the applet of the latest version, an image and  
10 animation can be displayed.

When the above mentioned system event which is not a starting event occurs, it is determined whether or not it is a destroy event (S19). If it is a destroy event, the terminating process is  
15 performed (S20). The terminating process deletes the program of the applet stored in the main memory as described above, reads the applet of the latest version from the server 1, and stores it.

If it is not determined to be a destroy event  
20 (S19), a specified event process is performed (S21).

If an applet is set in an active state as described above according to the present invention, or if the version number of an applet is checked under a predetermined condition, for example, when  
25 a user event requiring the online process, and the

applet is not the latest version, then the applet is necessarily updated into the latest version. Therefore, the Web browser 6 can be operated by the applet of the latest version.

5           According to the present embodiment, the version number checking process is performed in the above mentioned starting method, etc., but is not limited to the described method.

10           The version number information according to the present embodiment contains the version information and the level information as shown in FIG. 2, but can be formed by the version information only.

15           According to the present embodiment, the server 1 of the system is the sales office server 11 of a bank, and the client 2 is the window terminal 12 of a bank. However, the present invention is not limited to the above mentioned bank system, but can be applied to other fields  
20           such as insurance and policy systems.

          Furthermore, the applet latest version automatically setting system according to the present invention can also be realized using the system shown in FIG. 11. That is, as shown in FIG.  
25           11, a CPU (computer) 15 performs a process on the

above mentioned system using a program (data) provided by a hard disk 16.

As shown in FIG. 11, not only the program (data) provided by the internal RAM and hard disk 5 16, but also data is transmitted to and received from an externally connected storage medium. For example, a process can be performed according to the program provided from a storage medium 17 such as a magnetic disk, a magnetic tape, a floppy disk, 10 an optical disk, etc.

Furthermore, as shown in FIG. 11, a program (data) can be received from a provider 18 through a communications line.

As described above in detail according to the 15 present invention, the Web browser can be operated always using an applet of the latest version.

In addition, the transaction reliability can be greatly improved when a client and a server cooperates with each other in a bank online system, 20 etc. and an important transactions requiring high reliability is realized using a portable program such as a Java applet, etc.